



| LED LAMP SPECIFICATIONS: | | | | | | | | |
|--|----------------------------------|--|--|--|--|--|--|--|
| Lumens total flux | 450 lm | | | | | | | |
| Rated Wattage | 6W | | | | | | | |
| Rated luminous flux | 450 lm | | | | | | | |
| Nominal life time of the lamp | 35,000 hrs | | | | | | | |
| Colour temperature | 4200K | | | | | | | |
| Number of switching cycles before premature lamp failure | ≥17,500 | | | | | | | |
| Warm-up time up to 60 % of the full light output | Instant full light | | | | | | | |
| Dimmable | No | | | | | | | |
| LED array dimensions (L/W) | 140 x 60mm | | | | | | | |
| Nominal beam angle | 120° | | | | | | | |
| Rated power | 6W | | | | | | | |
| Rated lamp lifetime | 35,000 hrs | | | | | | | |
| Lamp power factor | >0.5 | | | | | | | |
| Lumen maintenance factor at end of nominal life | ≥0.70 | | | | | | | |
| Starting time | <0.1s | | | | | | | |
| Colour rendering | ≥80 | | | | | | | |
| Colour consistency | Within 6 step Macadam ellipse | | | | | | | |
| Rated peak intensity | 160cd | | | | | | | |
| Rated beam angle | 120° | | | | | | | |
| Voltage | 240V | | | | | | | |
| Not suitable for accent lighting | | | | | | | | |



6W IP65 LED POLYCARBONATE BULKHEAD

Energy efficient, long life alternative to traditional incandescent bulkheads

Polycarbonate construction

- Evenly diffused light output with no LED hotspots
- Top, bottom and rear 20mm knockout conduit entries
- Eterna 2 year warranty

230mm 105mm



| Code | Colour | Wattage | Colour Temp. | Lumens | Avg. Rated Life (Hrs) | IP Rating | Energy Rating |
|---------|--------|---------|-----------------|--------|--------------------------|--------------|------------------|
| BOPLED6 | Black | 6W | 4200K | 450 lm | 35,000 hrs | IP65 | A ⁺ |

