



ENERGY LABEL

Y DA
IE IA

енергия · ενεργεια

Eterna D039

A++
A+
A
B
C
D
E

B

21.20 kWh/1000h

LAMP SPECIFICATIONS:	
Lumens total flux	300 lm
Lumens 90° flux	260 lm
Rated Wattage	20W
Rated luminous flux	260 lm
Nominal life time of the lamp	2,000 hrs
Colour temperature	2700K
Number of switching cycles before premature lamp failure	10,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	No
Lamp dimensions (Ø/W)	30 x 8mm
Nominal beam angle	38°
Rated power	20W
Rated lamp lifetime	2,000 hrs
Lamp power factor	≥0.5
Lumen maintenance factor at end of nominal life	>75%
Starting time	<0.2s
Colour rendering	99%
Rated peak intensity	320cd
Rated beam angle	38°

LOW VOLTAGE TRIANGLE LIGHT

- Requires 1 x suitable 12V G4 M47 halogen capsule (included). Fitting is rated at 20W max
- This luminaire is compatible with bulbs of the energy classes: B to E and is sold with a bulb of the energy class: B
- Pressed steel construction
- Pre-wired with mini connector and 2.4 metres of silicone cable: easy installation
- Compatible with 5 way manifold block fitted on D034 transformer: flexible installation options
- Frosted glass diffuser: soft lighting effect

• M.O.M: 3 / O.P.Q: 45

Code	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	Energy Rating
D039	Brushed Nickel	20W	2700K	300 lm	2,000 hrs	IP20	B

Eterna D039



This luminaire is compatible with bulbs of the energy classes:



This luminaire is sold with a bulb of the energy class: **B**

